

788

105# PET UTILITY FILAMENT TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

A polyester film backed tape, laminated to uni-directional fiberglass filaments, and coated with natural rubber pressure-sensitive adhesive that adheres well to a variety of surfaces. The polyester film offers excellent scuff / abrasion and moisture resistance. Designed for the economy minded consumer. Provides excellent performance for light-duty general-purpose applications.

PRODUCT APPLICATION

Light duty bundling, packaging / carton sealing, reinforcing & strapping, unitizing / palletizing.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	57ga. Polyester (PET)
Adhesive	Natural Rubber / Resin
90° Adhesion to Steel (oz/in of width) PSTC-1	36 (9.9 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	105 (458 N/25mm)
Elongation (at break) PSTC-33	3.2%
Total Thickness (mils) PSTC-33	4.9 (0.124 mm)
Color	Natural



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/11

