REYNOLON[®] Shrink Film Packaging

5011

Typical Property Data

Soft Touch, Very Low Biaxial Shrinkage, Non-Food Packaging

5011 is a very low shrink, biaxially oriented film with low shrink force with outstanding sparkle and clarity for all nonfood products. This film can be used for the most delicate packages to prevent the curl or bend that occurs with higher shrink force films. It is a medium formulation that has excellent machinability and provides good seals to make your package look its best. Available single wound or center-folded.

Broportion	Units	Values													Test Method	
Properties		Values												ASTM	RTM	
		MD	CD													
Gauge	-	60		75		100		125		150		200				
Yield	Sq.In./Lb.	35,700		28,600		21,500		17,200		14,200		10,600		D646	1260	
Roll Weight	Lbs./In	1.68		1.68		1.67		1.67		1.69		1.70				
Density	gm/cc	1.31		1.31		1.31		1.31		1.31		1.31		D1505	1217	
Yield Strength	psi	3,500	3,300	3,500	3,300	3,500	3,300	3,500	3,300	3,500	3,300	3,500	3,300	D822	1254	
Tensile Strength	psi	6,700	6,700	6,700	6,700	6,700	6,700	6,700	6,700	6,700	6,700	6,700	6,700	D822	1254	
Elongation	%	140	180	150	180	150	180	150	180	150	180	150	180	D822	1254	
Shrinkage at 150°F	% Linear Dimensional Change	11	8	11	8	13	10	13	10	11	9	11	9	D2732	1257	
Shrinkage at 250°F		15	13	15	13	17	15	17	15	17	15	17	15	D2732	1257	
Shrink Force @ 250°F	psi	120	120	120	120	140	140	140	140	140	140	140	140	D1504	1249	
Haze	%	3.5		4		4		4		4		4			1262	
Seal Range (Lap)	°F	280-320		280-320		280-320		280-320		280-320		280-320			1251	
Slip-Coefficient of Friction	Static COF	0.2		0.2		0.2		0.2		0.2		0.2		D1894	1256	
	Kinetic COF	0.2		0.2		0.2		0.2		0.2		0.2		D1894	1256	

RTM - Reynolds Test Methods ASTM - American Society for Testing and Materials Revision: November 2005

Information contained herein is intended only for evaluation by technically skilled person, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but Reynolds Packaging LLC shall have no responsibility or liability for results obtained or damages resulting from such use. Reynolds Packaging LLC grants no license under, and shall have no responsibility or liability for rinfringement of, any patent or other proprietary right. Sales of Reynolds Packaging LLC products shall be independent and subject exclusively to warranties set forth in Reynolds Packaging LLC order acknowledgement. The foregoing may be waived or modified only in writing by an Reynolds Packaging LLC officer.

Special Gauges on Inquiry

