

534

MEDIUM GRADE FLATBACK TAPE

DESCRIPTION

A moisture resistant kraft flatback paper tape with an aggressive, pressure-sensitive natural/synthetic rubber adhesive. Designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Considered by many as the "Industry Standard." Excellent balance of machine and cross direction tensile and tear strength. Remains strong under moist conditions. Product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing

GOVERNMENT COMPLIANCE

Approved as packaging tape by both U. S. Postal Service and U.P.S (United Parcel Service).

PPP-T-42C, Type II
C.I.D. A-A-883B, Type II



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/10

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Kraft Flatback Paper
Adhesive	Natural/ Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-1	45 (12.3 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	40 (175 N/25mm)
Elongation (at break)	7%
Total Thickness (mils) PSTC-33	7.2 (0.18mm)
Operating Temperature Range Application	+50°F ~ +120°F (+10°C ~ +49°C)
Operating	+32°F ~ +180°F (0°C ~ +82°C)
Color	Brown

